

# VALUELINE

Distributed by Wulftec International Inc.

## Semi-Automatic Stretch Wrappers

The ValueLine pallet wrappers are designed to meet the most cost effective pallet wrapping applications.

Designed with affordability, versatility and reliability in mind, the ValueLine stretch wrappers ensure maximum efficiency while cutting labor and stretch film costs. **A good alternative to hand wrapping.**



Are you still manually wrapping loads because you think a stretch wrapping machine is too costly for your current needs? You may want to reconsider before dismissing this option.

HAND WRAPPING

VS

STRETCH WRAPPING  
WITH A VALUELINE

- |   |  |
|---|--|
| <input type="checkbox"/> Film waste                 | <input checked="" type="checkbox"/> Film savings... up to 66%    |
| <input type="checkbox"/> 10% pre-stretch            | <input checked="" type="checkbox"/> Up to 200% pre-stretch       |
| <input type="checkbox"/> 12 loads per hour          | <input checked="" type="checkbox"/> 40 loads per hour            |
| <input type="checkbox"/> Uneven packaging           | <input checked="" type="checkbox"/> Professional packaging       |
| <input type="checkbox"/> Manual labor               | <input checked="" type="checkbox"/> Minimal operator involvement |
| <input type="checkbox"/> Tedious and time consuming | <input checked="" type="checkbox"/> Quick and easy               |

WVL-075  
TENSION STRETCH ONLY  
PERFECT FOR PRE-STRETCHED  
FILM OR NETTING

WVL-100  
POWERED PRE-STRETCH  
STANDARD 200%



Companies that are hand wrapping and switch to stretch wrapping will see **significant savings in film usage**. As well, hand wrapping is a time-consuming and physically demanding operation. Stretch wrapping is easier and safer, while reducing product damage and labor. The cost of a stretch wrap machine is easily justified, even with 10-15 loads per day. A stretch wrap machine is excellent business sense... production rates go up, labor costs go down, wrapping is more consistent and there is more quality control over the wrapping process to ensure damage-free distribution.

To calculate your film savings, please refer to the Film Cost Calculator on our website... see "Calculate Your Savings!"

## Technical Specifications

	<b>WVL-100</b>	<b>WVL-075</b>
<b>PRODUCTION RATE*</b>	Up to 40 loads per hour	Up to 40 loads per hour
<b>MACHINE DIMENSIONS</b>	58"W x 100"L x 90 3/8"H	59"W x 92"L x 101"H
<b>MAX LOAD SIZE</b>	50"W x 50"L x 80"H (70.7" diagonal)	50"W x 50"L x 80"H (70.7" diagonal)
<b>MAX LOAD WEIGHT</b>	3,000 lbs	3,000 lbs
<b>APPROXIMATE SHIPPING WEIGHT</b>	985 lbs	970 lbs
<b>ELECTRICAL REQUIREMENTS</b>	120V/1/60 15A	120V/1/60 15A
<b>CONTROLS</b>	<ul style="list-style-type: none"> <li>- Programmable logic controller (PLC)</li> <li>- 24V control system</li> <li>- NEMA 4/12 enclosure</li> <li>- Current overload protection</li> <li>- Autoheight sensing photoeye</li> <li>- Power on/off switch and indicator light</li> <li>- Start/stop push button</li> <li>- Large emergency stop (push pull type)</li> <li>- Variable AC frequency drives</li> <li>- Manual carriage up/down function</li> <li>- Table jog</li> <li>- Variable table speed (10 RPM)</li> <li>- Carriage speed adjustment</li> <li>- Top and bottom wraps selectors – one selector for 1, 2, 3 wrap each</li> <li>- Film tension adjustment</li> <li>- Carriage limits: separate limit switches for up and down</li> </ul>	<ul style="list-style-type: none"> <li>- Programmable logic controller (PLC)</li> <li>- 24V control system</li> <li>- Current overload protection</li> <li>- Autoheight sensing photoeye</li> <li>- Power on/off switch and indicator light</li> <li>- Separate Start / Stop buttons</li> <li>- AC frequency drive for turntable</li> <li>- Variable table speed (10 RPM)</li> <li>- Limit switches for carriage limits</li> <li>- Manual carriage up/down function</li> <li>- Top and bottom wrap selectors – controlled by timer</li> <li>- Automatic and manual mode wrapping functions</li> <li>- Two wrapping modes, Spiral up and Spiral up/down</li> </ul>
<b>STRUCTURE</b>	<ul style="list-style-type: none"> <li>- Steel tower</li> <li>- Forklift portable base design (back only)</li> <li>- Structural steel construction</li> </ul>	<ul style="list-style-type: none"> <li>- Steel tower</li> <li>- Forklift portable base design (back only)</li> <li>- Structural steel construction</li> </ul>
<b>WRAP HEIGHT</b>	80" wrap height	80" wrap height
<b>FILM DELIVERY SYSTEM</b>	<ul style="list-style-type: none"> <li>- 20" NO-THREAD® Powered Pre-Stretch Carriage</li> <li>- 1/2 HP AC motor and 120V AC drive</li> <li>- Lifetime warranty on pre-stretch rollers' blue compound</li> <li>- Film force release for easy pull at start and end of cycle</li> <li>- 200% pre-stretch ratio (other pre-stretch ratio sold separately)</li> <li>- Electronic film tension control with analog sensor</li> <li>- Lexan roller cover for operator safety</li> </ul>	<ul style="list-style-type: none"> <li>- Adjustable mechanical tensioning brake</li> <li>- Easy film threading</li> </ul>
<b>FILM CARRIAGE DRIVE</b>	<ul style="list-style-type: none"> <li>- 1/2 HP AC motor and 120 V AC drive</li> <li>- Chain lift</li> </ul>	<ul style="list-style-type: none"> <li>- Chain driven</li> </ul>
<b>TURNTABLE</b>	58" dia. turntable 1/4" thick	58" dia. turntable 1/4" thick
<b>TURNTABLE DRIVE</b>	<ul style="list-style-type: none"> <li>- 0-10 RPM variable speed</li> <li>- 1/4 HP AC motor with 120V AC drive</li> <li>- Chain driven turntable</li> <li>- Electronic soft start/stop</li> <li>- Positive turntable alignment controlled by proximity sensor</li> </ul>	<ul style="list-style-type: none"> <li>- 0-10 RPM variable speed</li> <li>- 1/2 HP AC motor with 120V AC drive</li> <li>- Chain driven turntable</li> <li>- Electronic soft start/stop</li> <li>- Positive turntable alignment</li> </ul>
<b>TECHNICAL INFORMATION</b>	<ul style="list-style-type: none"> <li>- The machine is provided with a manual including electro/mechanical schematics and drawings, troubleshooting guide &amp; installation instructions</li> </ul>	<ul style="list-style-type: none"> <li>- The machine is provided with a manual including electro/mechanical schematics and drawings, troubleshooting guide &amp; installation instructions</li> </ul>
<b>WARRANTY</b>	<ul style="list-style-type: none"> <li>- 1 year</li> <li>- Lifetime warranty on pre-stretch rollers' blue compound</li> </ul>	<ul style="list-style-type: none"> <li>- 1 year</li> </ul>



**WVL-100**  
20" NO-THREAD® POWERED  
PRE-STRETCH CARRIAGE  
LIFETIME WARRANTY ON PRE-STRETCH  
ROLLERS' BLUE COMPOUND



**WVL-075**  
NO PRE-STRETCH CARRIAGE



**WVL-100 PANEL**



**WVL-075 PANEL**

\*Production rate based on load size and configuration.

### DISTRIBUTED BY:

Wulftec International Inc.  
209 Wulftec, Ayer's Cliff  
Quebec, Canada, J0B 1C0  
Tel: 819 838-4232  
Toll Free: 1 877 WULFTEC (985-3832)  
Fax: 819 838-5539  
E-mail: wulftec@wulftec.com